

« QUICK-SLEEVE WRAPPER »



This compact sleeve wrapper shrink wraps products like boxes, bottles, cans etc. with a film track and shrinks it tightly.

Huge standard equipment:

- Compact machine: sleeve wrapper and shrinking tunnel as one compact unit
- Product loading table covered with stainless steel plate
- Top film reel with brake
- Proofed security sealing system with adjustable sealing and cooling time
- Reliable magnetic sealing jaw closing system
- Infinitely adjustable conveyor speed
- Infinitely adjustable shrinking temperature up to approx. 250°C
- Flexible machine as standing on lockable castors
- Painted with a strong and resistible colour

Suitable extras:

- Rotating conveyor bars
- Distance of conveyor bars 25 mm instead of 37 mm
- Teflon net belt
- Electronic control of shrinking temperature
- Extended gravity roller conveyor of 1 m length

Technical Dates:

	Model „150“	Model „200“
Sealing width:	400 mm	400 mm
Width of conveyor belt:	340 mm	340 mm
Tunnel passage in height:	150 mm	200 mm
Heating capacity:	4 kW	4 kW
Required space:	only approx. 1,65 x 0,8 m	only approx. 1,65 x 0,8 m
Power supply:	400 V, 3 Ph, N, E	400 V, 3 Ph, N, E
Weight:	approx. 120 kg	approx. 130 kg